



FTQ4.0/15-LC Firefighting Floating
Water Pump

Main Features

- Materials: aluminum alloy main pump housing, bronze impeller, stainless steel pump shaft
- A filter is added to the bottom of the pump body to filter out debris in the water
- Easy to operate and easy to carry

Advantages

The floating pump is small in size, light in weight, and simple and quick to operate. Water can be drawn directly from ponds, rivers, wells, pools and other water sources, with strong flexibility, large water output, long range, and easy maintenance. It is suitable for fire scenes or used by fire brigades to replenish fire engine tanks with water from outdoor natural water sources. It can also be used to pump out water from flooded areas and rooms and for other applications, e.g. agriculture, building sites, etc.

Specifications

Model		FTQ4.0/15-LC
Engine	Brand & Model	LONCIN 1P92F
	Number of Cylinder	1 Cylinder * 4 Strokes
	Cooling system	Forced Air Cooled
	Max. Output	11 KW (15HP)
	Fuel Type	Unleaded Gasoline (90#, 92#, 95#, ...)
	Fuel Tank Capacity	4 Liters (1.06 gal)
	Operating time	60 min
	Fuel System	Single Carburetor with Solenoid Valve
	Oil Tank Capacity	1.2 Liters (0.32 gal)
	Starting	Manual/ Electric/ Remote
Pump	Max. Flow	1500 l/min
	Pump type	Centrifugal pump, self-priming
	Max water lift	50m
	Suction Thread and Dia.	3" (80mm)
	Discharge Thread and Dia.	2-1/2" (65mm)
	Discharge Number	Single
Weight	Net Weight	55 kg (121 lbs)
Dimensions	Overall (Length x Width x Height)	830 x 770 x 490 mm

MODEL: FTQ4.0/15-LC
COMPANY: ZHEJIANG HUAQIU FIRE FIGHTING EQUIPMENT CO.,LTD
ENGINE: LONCIN 1P92F

Performance Curve

